



HOT WATER PRESSURE WASHER

OIL / DIESEL FIRED



Adjustable thermostat
up to 200°F with LED rocker
switch and hour/tach meter

American made
heavy duty 7000 PSI
rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame, with centre balanced lift hook (above industry standards)

Honda GX390 electric start w/ 18amp charge

triplex direct-drive general pump carries a **5-year warranty**

Adjustable pressure relief valve

12" oil drain hose for ease of maintenance

7-gallon, removable, rust-proof polyethylene fuel tank with fuel gauge in cap

Brake assembly

Marine sealed battery box with 55 AH AGM deep cycle battery

3/4"HD Threaded
mount axle

360° Hose reel
swivel bracket

POWERED by
HONDA



FEATURES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- 20% chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle



HEATING COIL

½" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends

5500PSI Rated, "Full Sized" 96' length for maximum heat rise and proper heat production

Stainless-steel coil skin provides extra durability and resists corrosion

12v DC Oil-fired Beckett burner with low voltage inhibitor, prevents burner from starting up if battery voltage is dropped

Mounting bracket for truck mounting

13" heavy-duty flat free tires

MODEL	GPM	PSI	CC's	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW4013HG	4	4000	389	HONDA GX390	330,000	GENERAL PUMP EZ4040	DIRECT	2.21 GPH	47"L x 31"W x 50"H	52"L x 36"W x 55"H	530