

Maximum power. Minimal noise.

- Provides both single and three-phase output
- Single-phase 240V output available in all voltage settings
- Ultra Quiet Technology
- ESI-exclusive Re-Air option regulates airflow to maintain constant temperature within the enclosure



GENERATORS

BUILT ARCTIC TOUGH

www.EquipmentSourceInc.com

Features & benefits

- Rugged, fuel-efficient Isuzu diesel engine
- 74 gallon fuel capacity
- Ultra Quiet Technology for class-leading sound level reduction
- Lightweight and compact to fit into tight spaces
- Provides both single and three-phase output
- Single-phase 240V output available in all voltage settings
- Low oil pressure and high coolant temperature result in automatic shut-down
- Thermal relay opens main circuit breaker to protect generator in case of overload
- Durable all-weather outer enclosure with powder coated exterior and stainless steel fasteners
- Two-way tank valve for easy connection with auxiliary tanks

Available mounting

- Skid mounted (standard)
- Trailer mounted

Options

- ESI-exclusive Re-Air attachment regulates airflow to maintain a constant temperature within the enclosure


Specifications

Generator type	Rotating field, brushless 3-phase synchronous alternator
Frequency	60 Hz
Output	Three-phase: 150 kVA / 120 kW Single-phase: 90 kW
Voltage	Three-phase: 208, 480 V Single-phase: 120, 240, 277 V
Current	Three-phase 208V: 416A Three-phase 480V: 180A Single-phase 120V: 361 A x 2 (ZigZag) Single-phase 240V: 361 A (ZigZag)